



The Leading Manufacturer of Premium Detention Hardware & Accessories


## NW 845HW HEAVY WEIGHT HINGE W/ HOSPITAL TIP

<b>Size:</b>	4 1/2" x 4 1/2" x 0.18" Thick
<b>Material:</b>	304 Stainless Steel (SS)
<b>Style:</b>	Full Mortise, Square Corner
<b>Finish:</b>	US32D
<b>Bearing Type:</b>	Ball Bearing
<b>Pin Type:</b>	Hospital Tip, Stainless Steel Non-Removable Pin (NRP)
<b>Load Capacity:</b>	250lb Door (3 Hinges)
<b>Mounting Screws:</b>	Machine Screw, 1/2 x 12-24 FH Wood Screw, 1 1/4 x 12 FH
<b>Standard:</b>	ANSI/BHMA A156.1



**Features:** Hospital Tip (HT) prevents hanging any objects on the tip of the hinge. HT hinges with Non-Removable Pin (NRP) are used in medical or security areas and psychiatric facilities to prevent tampering or injury.

**Application:** Heavy Weight Stainless Steel hinges are permitted for use on wide and heavy doors or doors with heavy use or unusual stress. They can also be used on listed fire rated or labeled door openings.



Northwest Specialty Hardware, Inc.  
15865 SE 114th Avenue, Suite C  
Clackamas, OR 97015  
Phone (503) 557-1881 Fax (503) 557-1885 Email: [sales@northwestsh.com](mailto:sales@northwestsh.com)

[www.northwestsh.com](http://www.northwestsh.com)



The Leading Manufacturer of Premium Detention Hardware & Accessories

## NW 845HWSC HEAVY WEIGHT SWING CLEAR HINGE W/ HOSPITAL TIP

<b>Size:</b>	4 1/2" x 4 1/2" x 0.18" Thick
<b>Material:</b>	304 Stainless Steel (SS)
<b>Style:</b>	Swing Clear, Full Mortise
<b>Finish:</b>	US32D
<b>Bearing Type:</b>	Ball Bearing
<b>Pin Type:</b>	Hospital Tip, Stainless Steel Non-Removable Pin (NRP)
<b>Load Capacity:</b>	250lb Door (3 Hinges)
<b>Mounting Screws:</b>	Machine Screw, 1/2 x 12-24 Wood Screw, 1 1/4 x 12
<b>Standard:</b>	ANSI/BHMA A156.1



**Features:** (1) Hospital Tip (HT) prevents hanging any objects on the tip of the hinge. HT hinges with Non-Removable Pin (NRP) are used in medical or security areas and psychiatric facilities to prevent tampering or injury. (2) Swing Clear (SC) hinges are designed to swing the door completely clear of opening when door is opened 95 degree. Swing Clear hinges allows maximum clearance for passage of beds, tables, wheelchairs, or other equipment through door openings.

**Application:** Heavy Weight Swing Clear hinges are recommended for use on high frequency and/or heavy wood or metal doors in schools, hospitals or other public buildings where heavy traffic is experienced.



Northwest Specialty Hardware, Inc.  
15865 SE 114th Avenue, Suite C  
Clackamas, OR 97015  
Phone (503) 557-1881 Fax (503) 557-1885 Email: [sales@northwestsh.com](mailto:sales@northwestsh.com)

[www.northwestsh.com](http://www.northwestsh.com)